TURF-SEEDER

BLEC TURF-SEEDER



- Well proven method of seeding
- Accurate seeding adjustable 5-50gms/m²
- Stainless steel seed metering system
- Heavy duty 3 point linkage frame
- Spacer rings standard on all Turf-Seeder models to allow better germination of seeds
- Front rake tines to loosen soil

The BLEC Turf-Seeder are based on a proven method of seed incorporation. The front notched ring rollers crush lumps and level the soil to create a firm surface also producing small pockets in the soil, ready to accept the grass seed, which is spread the full width of the worked area (not drilled into lines). The rear set of rollers split the shallow ridges formed by the front rollers – incorporating the seeds evenly in the top 12mm soil, and surface disturbance is kept to a minimum.

| Model | 1800 | 2100 | 2400 | 3000 |
|----------------------------------|-----------------------------------|-----------------------|-----------------------|--------------------------------------|
| Model Number | 124.180.000 | 124.210.002 | 124.240.002 | 124.305.002 |
| Tractor hp req | 30-65 | 40-70 | 50-90 | 60-100 |
| Working width cm (in) | 180cm (71") | 210cm (83") | 240cm (94") | 300cm (118") |
| Working depth | 5-20 mm (6/32-1/2") | | | |
| Speed | up to 12 km/h (7.4mph) | | | |
| Seed rates gms/m ² | 0-50gm ² | | | |
| Hopper capacity litres (gal) | 235 (52gal) | 265 (58gal) | 300 (66gal) | 400 (88gal) |
| Max output per hour | 21,600 m ² | 25,200 m ² | 28,800 m ² | 36,000 m ² |
| | (25,833 sq yds) | (30,139 sq yds) | (34,444 sq yds) | (40,056 sq yds) |
| Cast notched ring dia cm (in) | 28cm (11in) front 28cm (11") rear | | | 40cm (15.7")front 28cm (11") rear |
| Weight kg (lb) | 760kg (1675 lb) | 850kg (1874lb) | 950kg (2099lb) | 1535 (3384lb) |
| Dimensions WxLxH cm | 216 x 106 x 104 | 247 x 106 x 104 | 276 x 106 x 104 | 350 x 170 x 113 |
| (in) | (85 x 42 x 41") | (97 x 42 x 41") | (109 x 42 x 41") | (138 x 67 x 44") |
| Options | | | | |
| Ballast Weights 20kg (44lb) | 16 x 492.502.800 | 22 x 492.502.800 | 28 x 492.502.800 | |