



KUBOTA WALK BEHIND MOWER

W821R-PRO / W821-PRO

From trimming well-kept lawns to mowing rough grass, a self-propelled Walk Behind Mower combining high durability with high performance — built for pros!



W821R-PRO
(ROLLER TYPE)

W821-PRO
(WHEEL TYPE)

FEATURES



BBC (Blade Brake Clutch)

The standard blade brake clutch stops the blade quickly for added safety. This allows emptying of the 75 L grass bag safely without stopping the engine.



Shaft Drive

The shaft drive rear wheel/roller transmission greatly reduces maintenance work compared to belt-driven mowers. Additionally, the shaft-mounted shock absorber also reduces slippage due to rain or grass clumps.



Heavy Duty Deck

The deck is a heavy duty aluminium die cast construction, reinforced with replaceable deckwear high durability parts.




Front Bumper

A front bumper comes standard to protect the deck from the impact of hitting trees or other obstacles.

Aluminium wheels

Stylish, wide-rimmed aluminium wheels and bearings come standard for added protection against corrosion. The large wheels provide increased manoeuvrability and traction while still maintaining durability for high-performance operation.



Discharge Chute

The large discharge chute design allows the machine to handle even high-moisture grass.

SPECIFICATIONS

Model	W821-PRO		W821R-PRO	
Engine				
Model	HONDA GXV160			
Engine type	Air-cooled, 4-cycle OHV, Single-cylinder, petrol engine			
Fuel	Unleaded petrol for automobiles			
Displacement	163 cm ³			
Bore×Stroke	68 mm × 45 mm			
Max. output	3.2 kw / 3,600 rpm			
Max. torque	9.6 Nm / 2,500 rpm			
Operation speed	2,800 rpm			
Fuel tank capacity	1.8 L			
Engine oil capacity	0.65 L			
Ignition system	Transistorised magnet ignition			
Ignition plug	NGK : BPR 5 ES / DENSO : W 16 EPR-U			
Starting method	Recoil method			
Dimension				
Outside dimensions (L×W×H)	1,830 × 580 × 1,270 (mm)		1,810 × 580 × 1,260 (mm)	
Dry weight	62 kg		58 kg	
Wheel diameter	244 mm Aluminium wheel		Front	203 mm Aluminium wheel
			Rear	102 mm Steel roller
Traveling Speed	2-step gearshift		Speed: 1.0 m/sec	
	Low speed: 1.0 m/sec			
	High speed: 1.4 m/sec			
Mower				
Blade engagement	BBC (Blade Brake Clutch)			
Grass bag capacity	75 L			
Cutting width	530 mm			
Cutting height	22,32,42,52,62,72,82 mm (7 Position)		15,26,37,47,57,67,77 mm (7 Position)	

* The company reserves the right to change the above specifications without notice.



KUBOTA (U.K.) LIMITED

Domer Road Thame, Oxfordshire, OX9 3UN.
Phone Thame (01844) 268000 Fax(08702) 429677
E-mail: sales@kubota.co.uk

Web site: <http://www.kubota.co.uk>

Cat.No22160-01-UK Printed in Japan.Kubota eight corp. '13-Jan.