

AERATION MULTI SPIKE & LEVEL SPIKE

Model	Multi Spike 1200	Level Spike 1700	Level Spike 2200
Weight	402kg (884lbs)	410kg (902lbs)	504kg (1108lbs)
Working width	1.35m (53")	1.8m (71")	2.4m (94")
Working depth	up to 250mm (10")	up to 250mm (10")	up to 250mm (10")
Road width	1.45m (57")	1.86m (73")	2.47m (97")
Minimum Tractor hp required	Min. 18hp	Min. 35hp	Min. 45hp
Number of mounting discs	9	12	16
Standard supplied with	36 truckster knives + Rear Roller	48 deep slit knives	64 deep slit knives
Knives/coring tines number	Standard/Maximum	Standard/Maximum	Standard/Maximum
- Truckster knives	36/54	48/72	64/196
- Deep Slit knives	36/54	48/72	64/196
- Fine Slit knives	192/192	264/264	360/360
- Twisted Deep Slit knives	36/54	48/72	64/196
- Hollow Coring tine	54/108	72/144	96/192
Four knife sizes + Hollow Tine	Max. working depth	Thickness	
Deep Slit Knife	250mm	5mm	
Truckster Knife	200mm	3mm	
Fine Slit Knife	100mm	3mm	
Twisted Deep Slit Knife	250mm	5mm	
Hollow Tine	125mm	26mm Ø	

Twisted Deep Slit knives are designed in a twisted form so that a more aggressive slicing job can be done.

Optional items for 1200, 1700 & 2200 wheel kit & weight transfer system, Rear Roller.



The Multi Spike 1200 can be utilised with a wheel kit for transport (above left). In this configuration the Multi Spike can be used in conjunction with virtually any prime mover which has basic flow and return hydraulics.

The Multi Spike and Level Spike open the soil with different size knife options.

The optional weight transfer system ensures that the weight of the tractor is transferred on to the knives in hard soil conditions.

