

# PRODUCT RANGE

Technical specifications 2021



Battery Lawn Mowers

2

Mulching Lawn Mowers

11

Battery-System

4

Professional Lawn Mowers

12

Petrol Lawn Mowers

8













Scarifiers

15

Electric Lawn Mowers

10

# BATTERY LAWN MOWERS

	COMPACT LINE		COMFORT LINE		PRO LINE
	40-ACCU	43-ACCU	43-ACCU VARIO	47-ACCU VARIO	43-PRO ACCU
 Cutting width	40 cm	43 cm	43 cm	47 cm	43 cm
 Battery & power supply unit	Incl. Li-Ion 6Ah 40V & charger	Incl. 2x Li-Ion 4Ah 40V & charger	Incl. 2x Li-Ion 4Ah 40V & fast charger	Incl. 2x Li-Ion 6Ah 40V & fast charger	Incl. 2x Li-Ion 6Ah 40V & fast charger
 Battery life*	~ 45 min	~ 40 min	~ 30 min	~ 40 min	~ 48 min
 For mowing areas up to*	Up to 500 m <sup>2</sup>	Up to 600 m <sup>2</sup>	Up to 500 m <sup>2</sup>	Up to 700 m <sup>2</sup>	Up to 1.000 m <sup>2</sup>
 Central cutting height setting	Sixfold 2,4-7,5 cm	Sevenfold 2,2-8,0 cm	Eightfold 2,5-8,0 cm	Eightfold 2,5-8,0 cm	Eightfold 2,5-8,0 cm
 Grass collector capacity	44 l	55 l	45 l	45 l	45 l
 Mulching	-	-	○ BSA643	○ BSA644	-
 Handlebar height adjustable	Sixfold	Threefold	Threefold	Threefold	Threefold
 Drive system	-	-	Variable 2,0-4,0 km/h	Variable 2,0-4,0 km/h	-
 Wheels front/rear	Ball-bearing	Ball-bearing	Ball-bearing	Ball-bearing	Double Ball-bearing
 Weight	19 kg	22,5 kg	31 kg	33 kg	28,5 kg
 Material of mower deck	High grade polypropylene	Aluminium	Aluminium	Aluminium	Aluminium with steel inlet
Guaranteed sound power level $L_{WA}$ [dB(A)], according to 2000/14/EC	89	93	93	93	93
Noise emission pressure level at the handlebar $L_{pA}$ [dB(A)], according to EN 60335-2-77/ uncertainty according to EN ISO4871	78 3,0	81 3,0	80 3,0	81 3,0	79 1,5
Vibrations on handlebar $a_{hw}$ [m/s <sup>2</sup> ], according to EN 60335-2-77/ uncertainty according to EN 12096	1,0 0,5	0,5 0,25	1,0 0,5	1,0 0,5	1,0 0,5
Item number	SA1781	SA1782	SA521020	SA521520	SA601020

● Standard  
○ Accessory  
\* Depends on multiple factors such as mowing-habits, grass texture and cutting height.



COMPACT LINE  
**40-ACCU**



COMPACT LINE  
**43-ACCU**



COMFORT LINE  
**43-ACCU VARIO**



COMFORT LINE  
**47-ACCU VARIO**
























PRO LINE  
**43-PRO ACCU**



The driving speed of our battery lawn mowers with VARIO-Drive-System can be comfortably adjusted from the handlebar.



COMPACT LINE		COMPACT LINE		COMPACT LINE	
Hedge trimmer HC-61		Gras trimmer BC-30		Leaf blower LB-660	
 Cutter length	61 cm	 Cutting width	30 cm	 Air power	7 N
 Cutter distance	27 mm	 Cutting head	String	 max. air volume	660 m <sup>3</sup>
 Battery technology	Li-Ion 40V 4Ah / 40V 6Ah	 Battery technology	Li-Ion 40V 4Ah / 40V 6Ah	 Battery technology	Li-Ion 40V 4Ah / 40V 6Ah
 Battery life 4 Ah *	~ 80 min	 Battery life 4 Ah *	~ 40 min	 Battery life 4 Ah *	~ 26 min
 Battery life 6 Ah *	~ 120 min	 Battery life 6 Ah *	~ 60 min	 Battery life 6 Ah *	~ 40 min
 Weight with out battery	2,7 kg	 Weight with out battery	2,2 kg	 Weight with out battery	1,9 kg
Guaranteed sound power level L <sub>WA</sub> [dB(A)], according to 2000/14/EC	100	Guaranteed sound power level according to EN22868 (dB(A))	96	Guaranteed sound power level L <sub>WA</sub> [dB(A)], according to 2000/14/EC	104
Vibrations (m/s <sup>2</sup> ) in accordance with EN 60745-2-15	< 2,5	Vibrations (m/s <sup>2</sup> ) in accordance with EN22867	< 2,5	Vibrations (m/s <sup>2</sup> ) in accordance with EN 50636-2-100	< 2,5
 Battery & power supply unit	○	 Battery & power supply unit	○	 Battery & power supply unit	○
Item number	SA560020	Item number	SA561020	Item number	SA560520



HEDGE TRIMMER  
**HC-61**








GRASS TRIMMER  
**BC-30**



LEAF BLOWER  
**LB-660**

## BATTERY-SYSTEM

	BATTERY SYSTEM			
	Standard charger	Fast charger	Li-Ion Battery 4 Ah	Li-Ion Battery 6 Ah
 Battery technology			Li-Ion Battery	Li-Ion Battery
Output voltage	40 V	40 V	40 V	40 V
Max. capacity			4 Ah	6 Ah
 Battery life (~ min)			Depending on the use case	Depending on the use case
 Battery charging time Standard charger (80% / 100%)			90 min / 95 min	110 min / 200 min
 Battery charging time Fast charger (80% / 100%)			60 min / 80 min	65 min / 95 min
 Weight	0,72 kg	1,11 kg	1,25 kg	1,35 kg
Item number	SAA11781	SAA16509	SAA11780	SAA12250



### BATTERY-SYSTEM LITHIUM-ION BATTERY

The powerful and reliable lithium-ion battery provides power for excellent results. Available with 4Ah or 6Ah capacity - easily removable for charging.

The modern battery technology is a significant advantage for our environment: working with it is quiet and without exhaust gases or local exhaust emissions.



### BATTERY-SYSTEM FAST CHARGER

- Standard
- Accessory
- \* Estimate, depends on multiple factors

COMFORT LINE	
Hedge trimmer HC-66	
Motor type	Brushless DC motor (BLDC)
No load rotational frequency	4000 ± 10 % rpm
Housing material	Magnesium
Blade	Sharpened on both sides
Handle	Multifunction adjustable in 3 positions
Cutting width	660 mm
Guidance guard	Yes with suspension eye
Weight without battery	3,5 kg
Measured sound pressure level	$L_{PA} = 92,0 \text{ dB(A)}$ $k = 3 \text{ dB(A)}$
Guaranteed sound power level	$L_{WA} = 104 \text{ dB(A)}$
Vibration	$a_h = 3,2 \text{ m/s}^2$ $k = 1,5 \text{ m/s}^2$
Model number	SA560121

COMFORT LINE	
Chainsaw CS-25	
Motor type	Brushless DC motor (BLDC)
Chain speed	20 m/s
Chain stop time	< 0,2 s
Chain oil capacity	180 ml
Guide bar length	250 mm
Sword lengths	Included 250 mm & 350 mm
Weight without battery	3,8 kg
Measured sound pressure level	$L_{PA} = 92,0 \text{ dB(A)}$ $k = 3 \text{ dB(A)}$
Guaranteed sound power level	$L_{WA} = 104 \text{ dB(A)}$
Vibration	$a_h = 4,9 \text{ m/s}^2$ $k = 1,5 \text{ m/s}^2$
Model number	SA561521

COMFORT LINE		
Grass trimmer MS-63		
	String	Blade
Motor type	Brushless DC motor (BLDC)	
No load rotational frequency	6300 ± 10 % rpm	6800 ± 10 % rpm
Cutting head	String feed (Cutting line diameter 2,0mm)	Blade
Cutting path diameter	356 mm / 406 mm	254 mm
Handle	Bike handle	
Shoulder strap	Included	
Extra features	String & blade mountable Adjustable string length	
Weight without battery	4,5 kg	
Measured sound pressure level	$L_{PA} = 78,4 \text{ dB(A)}$ $k = 3 \text{ dB(A)}$	$L_{PA} = 82,8 \text{ dB(A)}$ $k = 3 \text{ dB(A)}$
Guaranteed sound power level	$L_{WA} = 96 \text{ dB(A)}$	$L_{WA} = 101 \text{ dB(A)}$
Vibration	$a_h < 2,5 \text{ m/s}^2$ $k = 1,5 \text{ m/s}^2$	
Model number	SA561121	

## BATTERY-SYSTEM NEW IN 2021

COMFORT LINE	
Leaf blower LB-934	
Motor type	Brushless DC motor (BLDC)
Maximal air speed	209 km/h
Maximal volume flow rate	934 m³/h
Speed Adjustment	Adjustable & lockable (with turbo button)
Weight without battery	2,15 kg
Measured sound pressure level	$L_{PA} = 87,8 \text{ dB(A)}$ $k = 3 \text{ dB(A)}$
Guaranteed sound power level	$L_{WA} = 98 \text{ dB(A)}$
Vibration	$a_h < 2,5 \text{ m/s}^2$ $k = 1,5 \text{ m/s}^2$
Model number	SA560621



HEDGE TRIMMER  
HC-66



CHAINSAW  
CS-25



GRASS TRIMMER  
MS-63



LEAF BLOWER  
LB-934

# PETROL LAWN MOWERS

	COMPACT LINE		COMFORT LINE						
	40-SPIRIT	43-COMPACT	43-A ECONOMY	47-VARIO	47-VARIO E	54-VARIO	54-VARIO E	54-K VARIO B	
Cutting width	40 cm	43 cm	43 cm	47 cm	47 cm	54 cm	54 cm	54 cm	
Engine Rated capacity (kW) Cutter bar speed (rpm)	Four-stroke 2,1 2800	Four-stroke 2,6 2800	Four-stroke 2,6 2800	Four-stroke 2,8 2800	Four-stroke 2,8 2800	Four-stroke 2,8 2800	Four-stroke 2,8 2800	Four-stroke 2,8 2800	Four-stroke- OHC 3,2 2800
For mowing areas up to	700 m <sup>2</sup>	800 m <sup>2</sup>	1000 m <sup>2</sup>	1500 m <sup>2</sup>	1500 m <sup>2</sup>	2500 m <sup>2</sup>	2500 m <sup>2</sup>	2500 m <sup>2</sup>	
Central cutting height setting	Sixfold 2,4-7,5 cm	Sevenfold 2,2-8,0 cm	Eightfold 2,5-8,0 cm	Eightfold 2,5-8,0 cm	Eightfold 2,5-8,0 cm	Eightfold 2,0-9,5cm	Eightfold 2,0-9,5cm	Eightfold 2,0-9,5cm	
TurboStar SABO Turbostar™-System	•	•	•	•	•	•	•	•	
Grass collector capacity	• 44 l	• 55 l	• 65 l	• 65 l	• 65 l	• 75 l	• 75 l	• 75 l	
Mulching	○ SA575	○ SA571	○ BSA632	○ BSA625	○ BSA625	○ SA609	○ SA609	○ SA610	
Blade Brake Clutch	-	-	-	-	-	-	-	•	
Handlebar height adjustable	Threefold	Threefold	Threefold with quick release	Threefold	Threefold	Threefold	Threefold	Threefold	
Electric start	-	-	-	-	•	-	•	-	
Drive system	-	-	Konstant 3,6 km/h	Variable 2,7-4,3 km/h	Variable 2,7-4,3 km/h	Variable 2,7-4,8 km/h	Variable 2,7-4,8 km/h	Variable 2,7-4,8 km/h	
Wheels front/rear	Ball- bearing	Ball- bearing	Ball- bearing	Ball- bearing	Ball- bearing	Ball- bearing/ Needle roller bearing	Ball- bearing/ Needle roller bearing	Ball- bearing/ Needle roller bearing	
Weight	22 kg	28,5 kg	35 kg	38 kg	42 kg	48 kg	51 kg	56 kg	
Material of mower deck	High grade polypropylene	Aluminium	Aluminium	Aluminium	Aluminium	Aluminium	Aluminium	Aluminium	
Guaranteed sound power level L <sub>WA</sub> [dB(A), according to 2000/14/EC	96	96	96	96	96	98	98	98	
Noise emission pressure level at the handlebar L <sub>pA</sub> [dB(A), according to EN ISO5395/ uncertainty according to EN ISO4871	82 3,0	85 3,0	83 3,0	83 3,0	84 3,0	86 3,0	86 3,0	86 3,0	
Vibrations on handlebar a <sub>hw</sub> [m/s <sup>2</sup> ], according to EN ISO5395/ uncertainty according to EN 12096	5,0 2,5	5,0 2,5	5,5 2,5	5,5 2,8	5,5 2,6	5,0 2,5	5,0 2,5	5,0 3,0	
Item number	SA201219	SA201019	SA211019	SA221519	SA221619	SA222520	SA222620	SA222720	

• Standard  
○ Accessory



COMPACT LINE  
**40-SPIRIT**



COMPACT LINE  
**43-COMPACT**



COMFORT LINE  
**43-A ECONOMY**



COMFORT LINE  
**47-VARIO**



COMFORT LINE  
**47-VARIO E**



COMFORT LINE  
**54-VARIO**















COMFORT LINE  
**54-VARIO E**



COMFORT LINE  
**54-K VARIO B**



# ELECTRIC LAWN MOWERS

	Cutting width
	Engine Rated capacity (kW) Cutter bar speed (rpm)
	For mowing areas up to
	Central cutting height setting
	SABO TurboStar™-System
	Grass collector capacity
	Mulching
	Handlebar height adjustable
	Drive system
	Wheels front/rear
	Weight
	Material of mower deck
Guaranteed sound power level $L_{WA}$ [dB(A)], according to 2000/14/EC	
Noise emission pressure level at the handlebar $L_{pa}$ [dB(A)], according to EN 60335-2-77/ uncertainty according to EN ISO4871	
Vibrations on handlebar $a_{hw}$ [ $m/s^2$ ], according to EN 60335-2-77/ uncertainty according to EN 12096	
Item number	

COMPACT LINE	
40-EL SPIRIT	43-EL COMPACT
40 cm	43 cm
Electric 1,3 kW 3000	Electric 1,5 kW 3000
600 m <sup>2</sup>	700 m <sup>2</sup>
Sixfold 2,4-7,5 cm	Sevenfold 2,2-8,0 cm
•	•
44 l	55 l
-	-
Threefold	Threefold
-	-
Ball-bearing	Ball-bearing
22 kg	27 kg
High grade polypropylene	Aluminium
96	96
83 3,0	82 3,0
1,0 0,5	1,0 0,5
SA754	SA1457















COMPACT LINE  
**40-EL SPIRIT**



COMPACT LINE  
**43-EL COMPACT**

• Standard  
◦ Accessory

	Cutting width
	Engine Rated capacity (kW) Cutter bar speed (rpm)
	For mowing areas up to
	Cutting height setting
	Anti-Vibration-System
	For extreme vegetation
	Handlebar height adjustable
	Drive system
	Wheels front/rear
	Weight
	Fuel capacity
	Material of mower deck
Guaranteed sound power level $L_{WA}$ [dB(A)], according to 2000/14/EC	
Noise emission pressure level at the handlebar $L_{pa}$ [dB(A)], according to EN ISO5395/ uncertainty according to EN ISO4871	
Vibrations on handlebar $a_{hw}$ [ $m/s^2$ ], according to EN ISO5395/ uncertainty according to EN 12096	
Item number	

COMFORT LINE	PRO LINE
JS 63 VARIO	53-PRO M VARIO SM
53 cm	53 cm
Four-stroke OHV 3,2 2800	YAMAHA Four-stroke-OHC 3,2 / 2800
2000 m <sup>2</sup>	5000 m <sup>2</sup>
Sevenfold per axis 2,0-9,7 cm	Sevenfold per axis 3,0-9,5 cm
-	•
-	•
Threefold	Threefold
Variable 2,5-5,2 km/h	Variable 2,0-3,5 km/h
Ball-bearing/ Needle roller bearing	Ball-bearing/ Bronze slide bearings
37,5 kg	51,5 kg
1,0 l	1,2 l
Steel	Steel
96	96
80 3,0	83 3,0
3,6 1,8	2,5 1,3
SA222019	SA322020

# MULCHING LAWN MOWER


















COMFORT LINE  
**JS 63 VARIO**



PRO LINE  
**53-PRO M VARIO** Yamaha

• Standard ◦ Accessory

		PRO LINE			
		43-PRO	47-PRO VARIO	54-PRO VARIO	54-PRO K VARIO B PLUS
	Cutting width	43 cm	47 cm	54 cm	54 cm
	Engine Rated capacity (kW) Cutter bar speed (rpm)	Four-stroke 2,6 2800	Four-stroke OHC 3,2 2800	Four-stroke-OHV 3,2 2800	Four-stroke OHC 3,2 2800
	For mowing areas up to	1500 m <sup>2</sup>	2500 m <sup>2</sup>	3500 m <sup>2</sup>	4000 m <sup>2</sup>
	Cutting height setting	zentral 8 Stufen 2,5-8,0 cm	Einzelrad 7 Stufen 2,5-8,0 cm	Einzelrad 8 Stufen 1,5-9,5 cm	Einzelrad 8 Stufen 1,5-9,5 cm
	Anti-Vibration-System	-	Engine-AVS •	•	•
	For extreme vegetation	-	•	•	•
	SABO Turbostar™-System	-	•	•	•
	Grass collector capacity	65 l	65 l	75 l	75 l
	Mulching	○ BSA645	○ BSA631	○ SA612	○ SA610
	Blade Brake Clutch	-	-	-	•
	Handlebar height adjustable	Threefold	Threefold	Twofold	Twofold
	Drive system	-	Variable 2,7-4,5 km/h	Variable 2,7-4,8 km/h	Variable 2,7-4,8 km/h
	Wheels front/rear	Ball-bearing	Ball-bearing/ Bronze slide bearings	Ball-bearing/ Bronze slide bearings	Ball-bearing/ Bronze slide bearings
	Weight	33 kg	49 kg	54 kg	63 kg
	Fuel capacity	1,0 l	1,2 l	1,0 l	6,0 l
	Material of mower deck	Aluminium with steel inlet	Aluminium with steel inlet	Aluminium with steel inlet	Aluminium with steel inlet
	Guaranteed sound power level L <sub>WA</sub> [dB(A)], according to 2000/14/EC	96	96	98	98
	Noise emission pressure level at the handlebar L <sub>pa</sub> [dB(A)], according to EN ISO5395/ uncertainty according to EN ISO4871	83 3,5	84 3,0	86 3,0	86 3,0
	Vibrations on handlebar a <sub>hw</sub> [m/s <sup>2</sup> ], according to EN ISO5395/ uncertainty according to EN 12096	7,0 3,5	2,5 1,3	2,5 1,3	2,5 1,3
	Item number	SA301020	SA321520	SA322520	SA322720



PRO LINE  
**43-PRO**



PRO LINE  
**54-PRO VARIO**

## PROFESSIONAL PETROL LAWN MOWERS Rear Discharge



PRO LINE  
**47-PRO VARIO**
















PRO LINE  
**54-PRO K VARIO B PLUS**

- Standard
- Accessory



PROFESSIONAL PETROL LAWN MOWERS

 Cutting width	43 cm	50 cm	50 cm
 Engine Rated capacity (kW) Cutter bar speed (rpm)	Four-stroke-OHV 3,2 2800	Four-stroke-OHV 3,2 2800	Four-stroke OHC 3,2 2800
 For mowing areas up to	2000 m <sup>2</sup>	4000 m <sup>2</sup>	5000 m <sup>2</sup>
 Cutting height setting	Fivefold per wheel 3,5-7,5 cm	Sevenfold per wheel 2,5-8,0 cm	Sevenfold per wheel 2,5-8,0 cm
 Anti-Vibration-System	-	•	•
 For extreme vegetation	•	•	•
 Mulching	-	○ BSA641 BSA633	○ BSA641 BSA633
 Handlebar height adjustable	Threefold	Threefold	Twofold
 Drive system	-	Constant 3,5 km/h	Variable 2,2-3,7 km/h
 Wheels front/rear	Ball-bearing	Ball-bearing/ Bronze slide bearings	Ball-bearing/ Bronze slide bearings
 Weight	28 kg	46 kg	51 kg
 Fuel capacity	1,0 l	1,0 l	6,0 l
 Material of mower deck	Aluminium with steel inlet	Aluminium with steel inlet	Aluminium with steel inlet
Guaranteed sound power level L <sub>WA</sub> [dB(A), according to 2000/14/EC	96	96	96
Noise emission pressure level at the handlebar L <sub>PA</sub> [dB(A), according to EN ISO5395/ uncertainty according to EN ISO4871	84 3,0	82 3,0	83 3,0
Vibrations on handlebar a <sub>hw</sub> [m/s <sup>2</sup> ], according to EN ISO5395/ uncertainty according to EN 12096	5,0 2,5	2,5 1,3	2,5 1,3
Item number	SA301119	SA312020	SA312120

- Standard
- Accessory

PRO <sup>LINE</sup>		
43-PRO S	52-PRO S A	52-PRO S K A PLUS
43 cm	50 cm	50 cm
Four-stroke-OHV 3,2 2800	Four-stroke-OHV 3,2 2800	Four-stroke OHC 3,2 2800
2000 m <sup>2</sup>	4000 m <sup>2</sup>	5000 m <sup>2</sup>
Fivefold per wheel 3,5-7,5 cm	Sevenfold per wheel 2,5-8,0 cm	Sevenfold per wheel 2,5-8,0 cm
-	•	•
•	•	•
-	○ BSA641 BSA633	○ BSA641 BSA633
Threefold	Threefold	Twofold
-	Constant 3,5 km/h	Variable 2,2-3,7 km/h
Ball-bearing	Ball-bearing/ Bronze slide bearings	Ball-bearing/ Bronze slide bearings
28 kg	46 kg	51 kg
1,0 l	1,0 l	6,0 l
Aluminium with steel inlet	Aluminium with steel inlet	Aluminium with steel inlet
96	96	96
84 3,0	82 3,0	83 3,0
5,0 2,5	2,5 1,3	2,5 1,3
SA301119	SA312020	SA312120



PRO<sup>LINE</sup>  
43-PRO S














PRO<sup>LINE</sup>  
52-PRO S A



PRO<sup>LINE</sup>  
52-PRO S K A PLUS

SCARIFIERS

 Blade-cylinder width	35 cm	38 cm	45 cm
 Engine Rated capacity (kW) Cutter bar speed (rpm)	Electric 1,6 kW 3000	Four-stroke-OHV 2,3 kW 3400	Four-stroke-OHV 3,7 kW 3300
 For mowing areas up to	700 m <sup>2</sup>	1500 m <sup>2</sup>	4000 m <sup>2</sup>
 Adjustment of working depth	Continuously variable	Continuously variable	Continuously variable
 Number of scarifier blades	15	15	19
 Collection bag available	○ SA350	○ SA561	-
 Fast release mechanism	•	•	•
 Wheels front/rear	Slide bearing	Ball-bearing	Ball-bearing
 Weight	20 kg	37 kg	44,5 kg
 Fuel capacity	-	2,0 l	3,6 l
 Material of mower deck	High grade polypropylene	Aluminium	Aluminium
Guaranteed sound power level L <sub>WA</sub> [dB(A), according to 2000/14/EC	87	98	98
Noise emission pressure level at the handlebar L <sub>PA</sub> [dB(A), according to EN 13684/ uncertainty according to EN ISO4871	78 3,0	83 3,0	82 3,0
Vibrations on handlebar a <sub>hw</sub> [m/s <sup>2</sup> ], according to EN 13684/ uncertainty according to EN 12096	1,5 0,8	4,7 2,3	6,5 3,3
Item number	SA726	SA230820	SA331520

- Standard
- Accessory

COMPACT <sup>LINE</sup>		PRO <sup>LINE</sup>
35-V EL	38-BV	45-220
35 cm	38 cm	45 cm
Electric 1,6 kW 3000	Four-stroke-OHV 2,3 kW 3400	Four-stroke-OHV 3,7 kW 3300
700 m <sup>2</sup>	1500 m <sup>2</sup>	4000 m <sup>2</sup>
Continuously variable	Continuously variable	Continuously variable
15	15	19
○ SA350	○ SA561	-
•	•	•
Slide bearing	Ball-bearing	Ball-bearing
20 kg	37 kg	44,5 kg
-	2,0 l	3,6 l
High grade polypropylene	Aluminium	Aluminium
87	98	98
78 3,0	83 3,0	82 3,0
1,5 0,8	4,7 2,3	6,5 3,3
SA726	SA230820	SA331520



COMPACT<sup>LINE</sup>  
35-V EL



COMPACT<sup>LINE</sup>  
38-BV



PRO<sup>LINE</sup>  
45-220