# **#Technical data**

Model		Z122R
Engine		<del>-1121</del>
Туре		Petrol, air-cooled V-Twin
Horsepower (Net)	kW/hp	14.1/19
Total displacement	cm <sup>3</sup>	726
Fuel tank capacity	GIII	12.2
Transmission	'	12.2
Туре		Independent T/M
		Hydro Gear EZT® (ZT-2200)
Supplier and model PTO drive system		Belt Drive
Speed control		2 hand levers with height and angle adjustment
· · · · · · · · · · · · · · · · · · ·		
Parking brake system Cog Loc/Hand Lever		
Tyre size Front		11 x 4 – 5 smooth
Rear		18 x 7.5 – 10 turf
Travelling speed range	1/-	0 – 10.5
Forward	km/h	
Reverse	km/h	0 – 6.4
Dimensions		1000
Overall length	mm	1,890
Overall width w/o discharge deflector	mm	1,075
Overall height	mm	1,650
Wheelbase	mm	1,235
Weight	kg	282
Mower deck		
Cutting width	cm (inch)	107 (42)
Discharge		Side (Mulching kit available as option)
Cutting height ranges	mm (inch)	38 – 108 (1.50 – 4.25)
Cutting height increments	mm (inch)	6 (0.25)
Deck pan depth	mm (inch)	114 (4.5)
Deck pan thickness	Ga. (mm)	11(3.0)
Deck construction		Fabricated
Mower location		Mid mount
Mounting method		Parallel linkages
Adjustment of cutting height		Dial adjustment system
Mower deck lifting method		Mechanical Foot Lift Pedal
Driving method		Belt Drive
Number of Blades		2
Washport		1
Fuel gauge		Sight Window type
Seat		18inch Deluxe High Back Seat
Rops		Standard. ISO21299
PTO clutch		Electromagnetic
Cup holder		Standard
Hour meter		Standard

# Kubota (U.K.) Limited

Dormer Road Thame, Oxfordshire, OX9 3UN

#### http://www.kubota.co.uk

This publication may not be reproduced in whole or in part in any form without the prior written consent of KUBOTA. It corresponds to the status at the time of going to press. The manufacturer reserves the right to change technical specifications without notice. Some of the parts shown in the publication are optional and are not part of the standard equipment. Information on warranty and safety as well as further product information can be obtained from the responsible KUBOTA authorized dealer.



# For Earth, For Life Kubota

# KUBOTA Z-SERIES

Z122R



The company reserves the right to change the above specifications without notice.

This brochure is for descriptive purpose only. Some of the items pictured in this brochure are optional, and not standard equipment.

Please contact your local Kubota dealer for warranty, safety or product information.

# The best is exactly good enough

A central feature of Kubota's Z122R-Series is the zero-turn principle, which makes these mowers uniquely manoeuvrable. Kubota has equipped these machines with additional features that guarantee their excellent cutting quality and impressive large-area performance.

## Roll bar as standard Total peace of mind: for your safety, Seat with high backrest the Z122R is equipped with a high and stable roll bar. The spacious upholstered operator's seat with its high backrest keeps **Easy-action steering levers** you comfortable even during extra-long mowing The two steering levers give you the operations. smooth, precise control you need for fine lawn trimming and working around trees and flower beds. For even greater ease of use, you can adjust the levers to suit your Adjustable seating position The seat rails allow you to move the operator's seat back and Handy cup holder forth over a wide range. This ensures that you can find the The integrated cup holder means that your drink is always seating position that offers you ready to hand. maximum comfort. Easy lifting and cutting height

# adjustment

The mower deck lifting system is operated by foot control making the operation very easy. Adjusting the cutting height is done via a dial gauge on the control panel.

The large operator platform has ample legroom. This also makes it easier for you to get on and off the machine.

**Generous legroom** 

# #Features



### One mowing deck for top results

The welded mowing deck with 107 cm working width and 114mm depth produces outstanding cutting quality at a professional level. The result is faster and better mowing.




## Optional mulching equipment

The optional mulching equipment transforms the standard mower into a high-precision mulching mower that produces the finest mulch and feeds it directly back into the turf.



#### **Ergonomic controls**

All levers and switches are clearly arranged for quick, easy and user-friendly access.



The cutting height can be adjusted in precise 6 mm steps by simply turning the control dial.



### Powerful engine

You can rely on the Kawasaki V-twin engine for every mowing job. Quiet and fuel-efficient, the engine delivers the power you need to get the job done, every time.



# Robust gearbox

The independent hydrostatic transmission (HST) delivers concentrated power and efficient transmission to the wheels.



### Simple maintenance

You can easily access the oil dipstick and air filter without removing a cover. As there are no lubrication points, servicing the machine is easy. You will also appreciate the practical cleaning connection. Whenever you want to wash off wet grass, all you have to do is connect the hose