


Verti-Drain® 1513

The lightweight Verti-Drain® 1513 can work to a depth of 6" / 150mm and is well suited to sensitive turf surfaces. The belt driven machine operates a high speed while giving a neat and consistent hole pattern. An optional rear roller can be added to aid preening



Specifications

SKU	111.215.013
Working width (m)	1.32
Working width (inch)	52
Max. Working depth (mm)	150
Max. Working depth (inch)	6
Working speed at hole spacing 65 mm	1.8
Working speed at hole spacing 2-1 2 inch (mph)	1.1
Weight (kg)	425
Weight (lbs)	937
Hole distance with 12 mm tines (mm)	55
Hole distance with 1 2 x 6 inch tines (inch)	1/2/08
Hole spacing distance driving direction (mm)	25 - 125
Hole spacing distance driving direction (inch)	1-May
Max diameter solid tine (mm)	12 x 150
Max diameter solid tine (inch)	1/2 x 6
Max diameter hollow tine (mm)	19 x 150
Max diameter hollow tine (inch)	3/4 x 6
Min. Tractor HP required	25
Min. lifting capacity (kg)	650
Min. lifting capacity (LBS)	1450
Max. capacity with spacing 65 mm (m² hr)	2388
Max. capacity with spacing 2-1 2 inch (ft² hr)	25703
Three-point hitch	3-point CAT 1
Rpm Max.	540
Gear case oil	80W90 - 0.9
Lubricant	EP 2